

## **BOARD AND BATTEN SHUTTERS**

BOARDS: Specify number of vertical boards. 3" minimum, 7"

maximum widths. 1/4" beveled side edges.

BATTENS: 2 or 3 horizontal or Z-Bar. 1/4" beveled edges. Placed 7"

from top or below arch springline, and 7" from bottom. 5" for shutters < 35". Battens extend to 3/8" from sides.

SIZES: Custom Sized for your windows to the 1/8".

Max Width: 48" Max Length: 108"

MATERIAL: Select Grade lumber: African Mahogany, Red Grandis,

Incense Cedar, Southern Yellow Pine.

Common Grade lumber: Rough Sawn Cedar

Composite: Extira. Composite shutters are limited to the Closed Board style. To appear as vertical boards V-grooves are routed out of a solid sheet of Extira.

FINISH: Unfinished: Ready for the customer to prime and paint.

Primed Wood: INSL-X Aqua Lock Plus Primer/Sealer

(grey in color)

Primed Composite: Premium Products Industrial "One Coat High Build", Water-based Acrylic Primer (grey in color)

Priming is free for Board and Batten style shutters.

Painted: Benjamin Moore's Corotech High Performance
Command Water-Borne Acrylic Urethane, Satin finish.

Choice of In-Stock color or custom color match.

Stain-Grade: Stain-Grade wood is hand selected best pieces of wood in lot. Staining services are not offered.

SHIPPING: Free for shutter sizes less than 76".


CUSTOM: Cutouts, Arch Top (specify arch springline), Batten Size,

Batten Placement, Shutter Thickness, Non-Beveled Edges

Email us your special requirements.



## STYLES:



- 2 Battens: Any composite size shutters, or wood shutters <55"</li>
- 2.3 Battens: Any material shutters
- 3. Z-Bar: Any material shutters
- Open Weave: Only wood shutters. 1/4" gap unless 1/2" or 3/4" is specified. If >55" a 3rd center or Z-Batten is required.

	Select Grade Lumber	Common Grade Lumber	Composite
Boards	I" thick x varied width	3/4" thick x varied width	1" thick x varied width
Battens	1" thick x 3-1/2" tall	3/4" thick x 3-1/2" tall	5/8" thick x 3-1/2" tall